




BASETTE B-DIREZIONALI

PER FASCETTE FINO A 3.6 mm


CON ADESIVO Speciale



Naturale



Nero



APPLICAZIONI

Ancoraggio di cavi e tubi
Civile industriale hobbistica.

CARATTERISTICHE

Supporto adesivo in schiuma base gomma.
Temperatura minima applicazione **+10°**.
Resistenza al calore: del B-adesivo **-40°+60°**
Su richiesta: variante in PA 6.6



**CONFORMI ALLA NORMATIVA
EUROPEA ROHS**



VANTAGGI

Facilità di posa.
Applicabile su quasi tutti i tipi di materiali.
Adatte per fascette fino a: vedi specifiche

MATERIALE = ABS



**TENUTA FIAMMA
UL94 HB**






**APPLICAZIONE
IMMEDIATA**

CODICE Naturale	CODICE Nero	CONFEZIONE pz.			IMBALLO pz.	MISURA FASCETTA
1104HA00AP	1104HA01AP	25	50	100	10.000	MM. 3,6
1105HA00AP	1105HA01AP	25	50	100	5.000	MM. 4,8

PER ALTRI COLORI O MATERIALI DISPONIBILI CONTATTACI

ABS HOLDER	
Material	ABS
Color	natural
UL Class	UL94HB
UI Yellow Card	E 108538
Temperatur ABS	-30° to + 80°C
max. short time temperatur	+80°C
ADHESIVE DATA	
Foam	Polyethylene closed cell
Adhesive	SPECIAL
Foam density kg/m ³	100
Tensil strength N/cm ²	100
Service temperatur	-40°C to + 60°C
Application temperature	-15°C to + 40°C

REVISIONS			
REV	DATE	18/11/2019	BY
DESCRIPTION			



DOUBLE ADHESIVE TAPE
(THICKNESS 1.0 mm)

				TITLE SELF-ADHESIVE CABLE TIE MOUNT	
				MATERIAL ABS / PA 6.6	DATE 18/11/2019
				ADESIVO SPECIAL	DRAWN A.G.
PART NUMBER 1104HA00AP		DRAWINGNUMBER 19.1104.G		STANDARD COLOR NATURAL / BLACK	CHECK
SIZE A4	SCALE NTS	UNIT mm	REV A	UNLESS OTHERWISE SPECIFIED TOLERANCE SEE ABOVE	APPROVED