



SUPPORTI A VITE PA 6.6 PER FASCETTA

APPLICAZIONI

Posa di cavi e fili su superfici piane.
Civile industriale hobbistica.

VANTAGGI

Facilità di posa per cavo o fili
Applicabile su quasi tutti i materiali.

CARATTERISTICHE


MATERIALE = PA .6.6



Bianco



Nero



CONFORMI ALLA NORMATIVA
EUROPEA ROHS II



TENUTA FIAMMA
UL94-V2





APPLICAZIONE
IMMEDIATA

CODICE Naturale	CODICE Nero	Misura max fascetta	CONFEZIONE pz.	IMBALLO pz.	
2513AA00S	2513AA00S	mm 9	100	1.000	
				10.000	

PER ALTRI COLORI O MATERIALI DISPONIBILI CONTATTACI

HOLDER		REVISIONS		
Material	NYLON PA 6.6	REV	DATE 12/11/2019	BY A.G.
Color	natural	DESCRIPTION		
UL Class	UL94HB			
UI Yellow Card	E 108538			
Temperatur POLIAMIDE	-40° to + 100°C			
max. short time temperatur	+ 110°C			



AGSPLAST

AGSPLAST				TITLE SELF-ADHESIVE CABLE CLIP	
				MATERIAL NYLON 66 UL94-V2	DATE 12/11/2019
				ADESIVO STANDARD ADHESIVE RUBBER BASE	DRAWN A.G.
PART NUMBER 2513AA00S		DRAWING NUMBER 19.2513.G		STANDARD COLOR NATURAL / BLACK	CHECK
SIZE A4	SCALE NTS	UNIT mm	REV A	UNLESS OTHERWISE SPECIFIED TOLERANCE SEE ABOVE	APPROVED